

## AMENDMENTS TO THE CLAIMS:

The following listing of claims will replace all prior versions and listings of claims in the application.

Claim 1 (Withdrawn)      A tufted good comprising

- (1)    a greige good comprising one or more fibers tufted into a primary backing, said greige good having a face surface and a back surface;
- (2)    a precoat having a face surface and a back surface, wherein the face surface of said precoat is adhered to the back surface of said greige good;

and

- (3)    a flexible film laminated to the back surface of said precoat after treatment via corona-discharge at a power density of 0.2 to 20 Ws/cm<sup>2</sup>.

Claim 2 (Withdrawn)      The tufted good of Claim 1, additionally comprising (2)(a) a foam layer adhered to the back surface of the precoat; wherein said corona-discharge treated flexible film is laminated to the back surface of the foam layer.

Claim 3 (Withdrawn)      The tufted good of Claim 1, additionally comprising (4) a foam layer adhered to the back surface of (3) said corona-discharge treated flexible film.

Claim 4 (Withdrawn)      The tufted good of Claim 1, wherein said precoat comprises a reactive polyurethane system.

Claim 5 (Withdrawn)      The tufted good of Claim 2, wherein said foam layer comprises a reactive polyurethane system.

Claim 6 (Withdrawn)      The tufted good of Claim 3, wherein said foam layer comprises a reactive polyurethane system.

Claim 7 (Withdrawn)      The tufted good of Claim 1, wherein said flexible film is a polyolefin film.

Claim 8 (Withdrawn)      The tufted good of Claim 1, wherein said flexible film has a thickness of about 0.025 mm to about 1 mm.

Claim 9 (Withdrawn)      The tufted good of Claim 1, wherein the power density of the corona-discharge is from 0.5 to 10 Ws/cm<sup>2</sup>.

Claim 10 (Withdrawn) A tufted good comprising:

- (1) a greige good comprising one or more fibers tufted into a primary backing, said greige good having a face surface and a back surface;
  - (2) a foam having a face surface and a back surface, wherein the face surface of said foam is adhered to the back surface of said greige good;
- and
- (3) a flexible film laminated to the back surface of said foam after treatment via corona-discharge at a power density of 0.2 to 20 Ws/cm<sup>2</sup>.

Claim 11 (Withdrawn) The tufted good of Claim 10, wherein the foam layer comprises a reactive polyurethane system.

Claim 12 (Withdrawn) The tufted good of Claim 10, wherein said flexible film is a polyolefin film.

Claim 13 (Withdrawn) The tufted good of Claim 10, wherein said flexible film has a thickness of about 0.025 mm to about 1 mm.

Claim 14 (Withdrawn) The tufted good of Claim 10, wherein the power density of the corona-discharge is from 0.5 to 10 Ws/cm<sup>2</sup>.

Claim 15 (Canceled)

Claim 16 (Currently Amended) ~~The A process of Claim 15 for producing a tufted good comprising:~~

(A) treating a flexible film with corona-discharge at a power density of 0.2 to 30 Ws/cm<sup>2</sup>;

(B) contacting the , wherein the corona-discharge treated flexible film is contacted with an uncured or a partially cured back surface of a foam layer which is adhered to the back surface of a precoated greige good, wherein the precoat comprises a reactive polyurethane system;

and

(C) curing the article formed in (B).

Claim 17 (Canceled)

Claim 18 (Currently Amended) The process of Claim ~~45~~ 16, wherein the curing is at temperatures of from about 65 to about 150°C for about 2 to 10 minutes.

Claim 19 (Canceled)

Claim 20 (Original) The process of Claim 16, wherein the foam layer comprises a reactive polyurethane system.

Claim 21 (Canceled)

Claim 22 (Currently Amended) The process of Claim ~~45~~ 16, wherein said flexible film is a polyolefin film.

Claim 23 (Currently Amended) The process of Claim ~~45~~ 16, wherein said flexible film has a thickness of about 0.025 mm to about 1 mm.

Claim 24 (Currently Amended) The process of Claim ~~45~~ 16, wherein the power density of the corona-discharge is from 0.5 to 10 Ws/cm<sup>2</sup>.

Claim 25 (Previously presented) A process for producing a tufted good comprising:

- (A) treating a flexible film with corona-discharge at a power density of 0.2 to 20 Ws/cm<sup>2</sup>;
- (B) contacting the treated flexible film with an uncured or a partially cured back surface of a foam layer adhered to a greige good;
- and
- (C) curing the article formed in (B).

Claim 26 (Canceled)

Claim 27 (Original) The process of Claim 25, wherein the curing is at temperatures of from about 65 to about 150°C for about 2 to 10 minutes.

Claim 28 (Original) The process of Claim 25, wherein said flexible film is a polyolefin film.

Claim 29 (Original) The process of Claim 25, wherein said flexible film has a thickness of about 0.025 mm to about 1mm.

Claim 30 (Original) The process of Claim 25, wherein the power density of the corona-discharge is from 0.5 to 10 Ws/cm<sup>2</sup>.